

# Double Row Ball Slewing Bearing with External Gear

No.	Boundary Dimension			Bearing Type	Related Dimension												Gear Parameter					Weight kg ≈
	d	D	T		D1	d1	d2	Dwp	H	h	n1	n2	n3	φ 1	φ 2	φ 3	da	b	m	Z	x	
1	820	1150	125	6787/820G	1100	880	1020	990	130	5	2×2	1	14/4	M10×1	1	25/22	1206	75	12	99	-0.25	508
2	978	1262	124	021.30.1120.12	1218	1022	1159	1120	114	29	6	36	36	M10×1	22	22	1318	80	10	129	0.5	391
3	1074	1426	160	021.40.1250.12	1374	1126	1300	1250	150	39	8	40	40	M10×1	26	26	1497.6	90	12	122	0.5	726
4	1224	1576	160	021.40.1400.12	1524	1272	1450	1400	150	39	8	40	40	M10×1	26	26	1644	90	12	134	0.5	803
5	1224	1576	160	022.40.1400.12	1524	1272	1450	1400	150	39	5	40	40	M10×1	26	26	1649.2	90	14	115	0.5	809
6	1424	1776	160	022.40.1600.12	1724	1476	1650	1600	150	39	5	45	45	M10×1	26	26	1852.8	90	16	113	0.5	967
7	1600	2000	175	6787/1600G	1920	1675	1840	1790	190	15	4	20	10	M10×1	38	38	2066.4	120	14	146	-0.2	1531
8	1600	2000	175	6788/1600G	1920	1675	1840	1790	190	15	4	24	24	M10×1	32	32	2154.6	140	6	358	-0.45	1576
9	1624	1976	160	022.40.1800.12	1924	1676	1836	1800	150	39	5	45	45	M10×1	26	26	2060.8	90	16	126	0.5	1088
10	2135	2524	185	9787/2135	2436	2215	2331	2333	170	15	12	68	64	M10×1	39	M30	2616	147	20	128	0.5	1900
11	2135	2524	185	9787/2135K	2436	2215	2331	2333	170	15	6	68	64	M10×1	39	M30	2616	147	20	128	0.5	1900
12	2209	2470	90	021.25.2285.03	2340	2245	2306	2286	64	26	4	24	20	M10×1	M16	M16	2420	70	10	240	0	372
13	2285	2715	190	021.50.2500.12	2649	2351	2538	2500	178	47	8	56	56	M10×1	33	33	2804	120	18	153	0.5	2031
14	2570	3040	195	9787/2570	2885	2665	2776	2778	165	15	8	94	96	M10×1	39	M36	3141.6	170	22	140	0.5	2730
15	3405	3765	185	6789/3405G	3700	3465	3638	3570	185	45	12	48	48	M12×1.25	35	35	3852	120	18	212	0	2632
16	4470	5184	250	022.60.4700.03	4910	4565	4759	4700	238	65	10	60	60	M10×1	33	33	5184	155	18	286	0	7630